

# Declaration of Food Contact Conformity

Semi-Finished Plastic Products



## CENTRODAL C FG RAL 5017 / POM C FG RAL 5017

Material:	CENTRODAL C FG RAL 5017 / POM C FG RAL 5017
Article Group:	04
Composition:	Polyoxymethylene copolymer

We confirm that the above-named **semi-finished product** complies with the requirements

- Of the European Regulation (EC) No. 1935/2004 and the German Food and Feed Code (LFGB)
- Of the European Regulation (EC) No. 10/2011 (replaces EC Directive 2002/72/EC) resp. German Consumer Goods Ordinance

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017 blue can be freely used for the production of final products for repeated contact with all food categories. Products manufactured with it permit use under all contact conditions, including heating at 70 °C for up to 2 hours or heating at 100 °C for up to 15 minutes, which is not followed by long-term storage at room temperature or cooling.

The Regulation (2023/2006EC) on Good Manufacturing Practice (GMP) establishes rules for manufacturing materials and articles that are intended to come into contact with food. That means during the production processes, Centroplast is subject to the philosophy of GMP quality security system, quality control system and documentation.

The products above do not contain any “dual use” additives according to EU regulation No 1334/2008.

The traceability of our semi-finished product is in accordance with Regulation (EC) No.1935/2004 guaranteed for all production stages. Our food grade semi-finished products are marked with the “glass & fork” symbol and accompanied with the conformity declaration document, certificate of conformity incl. production order number.



### 1.0 Audit scope for migration tests on account of the use

It was used a mixed sample of equal proportions of the colours RAL 5002 and RAL 5017 for testing. The determination was made according to methods 80.30-1(EC) to 80.30-18(EC) of the official collection of examination procedures in § 64 LFGB [Food and Feed code]. The migration tests were carried out under the standard tests OM 3 (2 h, 70 °C) defined in Table 3 of Regulation (EC) No.10/2011.

10% ethanol was used as food simulants. There was 200 ml food simulant per dm<sup>2</sup> surface used. Since it concerns a re-usable material, migration attempts were carried out 3 times with the same test samples. The compliance with food additive specifications is to be judged on the basis of the results obtained from the third test.

# Declaration of Food Contact Conformity

Semi-Finished Plastic Products



## CENTRODAL C FG RAL 5017 / POM C FG RAL 5017

### 2.0 Test results of the migration tests according to (EC) No. 10/2011

#### 2.1 Global Migration

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
10% Ethanol (3 x 2 h, 70 °C)	< 1 mg/dm <sup>2</sup>	10 mg/dm <sup>2</sup>
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

#### 2.2 Specific Migration

The material was tested on the basis of the information presented on the recipe for compliance with the migration limit value for 1,3-Dioxolan, 1,3,5-Trioxan, Formaldehyde, Triethylenglykolbis (3-(3-tert.-butyl-4-hydroxy-5-methylphenyl)propionat und Melamine.

##### Migration of 1,3-Dioxolan

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
10% Ethanol (3 x 2 h, 70 °C)	< 0,1 mg/dm <sup>2</sup>	5 mg/kg food (=0,83 mg/dm <sup>2</sup> )
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

##### Migration of 1,3,5-Trioxan

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
10% Ethanol (3 x 2 h, 70 °C)	< 0,1 mg/dm <sup>2</sup>	5 mg/kg food (=0,83 mg/dm <sup>2</sup> )
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

##### Migration of Triethylenglykolbis (3-(3-tert.-butyl-4-hydroxy-5-methylphenyl)propionat

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
10% Ethanol (3 x 2 h, 70 °C)	< 0,1 mg/dm <sup>2</sup>	9 mg/kg food (=1,5 mg/dm <sup>2</sup> )
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

##### Migration of Melamine

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
10% Ethanol (3 x 2 h, 70 °C)	< 0,1 mg/dm <sup>2</sup>	2,5 mg/kg food (=0,42 mg/dm <sup>2</sup> )
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

The noted data correspond to our latest state of knowledge. The suitability of the products for special applications cannot be guaranteed legally binding, due to the a.m. properties

# Declaration of Food Contact Conformity

Semi-Finished Plastic Products



## CENTRODAL C FG RAL 5017 / POM C FG RAL 5017

Migration of Formaldehyde		
CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Result	Max. permitted migration*
Distilled Water	< 0,1 mg/dm <sup>2</sup>	15 mg/kg food (=2,5 mg/dm <sup>2</sup> )
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance		

### 2.3 Colourfastness

CENTRODAL C FG RAL 5017 / POM C FG RAL 5017	Odour
Distilled Water (2 h, 70 °C)	no
3% Acetic acid (2 h, 70 °C)	no
10% Ethanol (2 h, 70 °C)	no
Vegetable oil (2 h, 70 °C)	no
(*) Regulation (EC) No. 10/2011 resp. German Consumer Goods Ordinance	

**The user is to be referred to the abovementioned limitations that mean the corresponding semi-finished product is only valid with this conformity declaration and the corresponding certificate of conformity incl. production order number.**

This conformity declaration is based on the extensive test results dated 07.05.2012.

#### General Notice:

For our extensive delivery program, it is not possible to measure each semi-finished product. The tests are carried out on submitted articles of the article groups. Moreover, Centroplast makes sure that generally only raw materials with corresponding suitability notices are used. Our statements are supported by the documents prepared by our suppliers' tests and migration tests carried out by third parties. It is the distributor's responsibility to test the suitability of the plastic material components made for or from our products for the intended use in the food area:

- whether the physical characteristics of the plastic material are appropriate for the intended food
- compliance with the migration limits
- possible influence of the material on the chemical characteristics of the food
- compliance with the requirements of statutory regulations
- need for appropriate cleaning of the produced work pieces before the first contact with food
- removal of the extrusion skin of the semi-finished product

The information of this conformity declaration is based on our current status and cannot be raised as a guarantee declaration. We do not assume any liability for the completeness and accuracy of the information presented here.

The Company marketing the products shall be responsible for compliance with existing laws and regulations. In case of changes in the law, guidelines, ordinances, raw materials, processing procedures, etc., this declaration shall be re-evaluated.

Insofar as changes are made, Centroplast shall make these available appropriately. Previous declarations shall then lose their validity.

Centroplast Engineering Plastics GmbH – Unterm Ohmberg 1 – 34431 Marsberg – Germany  
[application@centroplast.de](mailto:application@centroplast.de) – [www.centroplast.de](http://www.centroplast.de)